

# Paris PAR-GAR.

## Power & cooling

Total power supply to site: 3000 kVA
Total generator power: 3200 kVA in N+1

configuration

Total UPS power: 2000 kVA in 2N configuration

Cooling type: DX

**Total cooling:** 1600kW in N+1 configuration

## **Building specification**

Gross size of data centre: 760 m<sup>2</sup> Net size of customer space: 2000 m<sup>2</sup> Building type: Steel frame warehouse

**Building tenure:** Leasehold **Number of data suites:** 3 **Suit expansion available:** Yes

**Uniform distributed loads:** 1000 kg/m<sup>2</sup> **Max raise floor height:** 400 mm for

1 x room only

#### Connectivity

This facility provides triple fibre entry and diverse paths within the building connecting directly to the Interoute 100g backbone network. Our colocation facilities are designed to deliver laaS and virtualised services as part of an integrated platform; delivering any service(s) over any access type, allowing in-life service changes, enabling you to connect your people, buildings and data in a way that suits you.

#### Location

Address: 34 rue des Gardinoux, 93300,

Aubervilliers, France

**Location:** 48°54′24.52″N 2°22′04.43″E **Email:** salesteam@interoute.fr **Website:** www.interoute.fr

## Security & support

24 x 7 x 365 helpdesk 24 x 7 x 365 hands & eyes 24 x 7 x 365 on site security guard Critical facility monitoring Perimeter & internal CCTV Intrusion detection Customer access list

## Fire detection & suppression

Early smoke detection system FirePro suppression system

#### **Colocation services**

**SLA:** 99.999% power availability

Service type: Data centre

½ rack Rack Footprint

Power feed: Active A+B feed

**AC power:** Supports 2-3 kW per rack as

standard

**DC power:** 10A, 20A & 40A power configurations available on demand **Cage & private suites:** Configuration

on demand

#### 31 Colocation centres across

#### **Europe including**

Amsterdam • Berlin • Brussels • Geneva • Ghent • Madrid •

Milan • Munich • London • Rome • Stockholm • Zurich





ISAE 3402/ SSAE 16 Type II



PCI DSS compliant

